Interim Guidance for Electric and Hybrid-Electric Vehicles Equipped With High Voltage Batteries (Law Enforcement/Emergency Medical Services/Fire Department)

Electric and Hybrid-Electric Vehicle Considerations

In the event of damage to or fire involving an electric vehicle (EV) or hybrid-electric vehicle (HEV):

- Always assume the high voltage (HV) battery and associated components are energized and fully charged.
- · Exposed electrical components, wires, and HV batteries present potential HV shock hazards.
- Venting/off-gassing HV battery vapors are potentially toxic and flammable.
- Physical damage to the vehicle or HV battery may result in immediate or delayed release of toxic and/or flammable gases and fire.

Vehicle Shutdown and High Voltage System Disabling

IDENTIFY VEHICLE

• Determine if the vehicle is an electric or hybrid-electric vehicle, and if it is, advise Dispatch and all responders that an electric or hybrid-electric vehicle is involved.

IMMOBILIZE VEHICLE

- Always approach vehicle from the sides to stay out of potential travel path. It may be difficult to determine if the vehicle is running due to lack of
 engine noise.
- If possible, chock the tires, place the vehicle into Park, and set the parking brake.

DISABLE VEHICLE

- Turn off the vehicle, activate hazard lights, and move vehicle keys at least 16 feet away from the vehicle.
- If your local standard operating procedures (SOPs) allow it and you are properly trained and equipped, disconnect the vehicle's 12-volt battery. CAUTION: Safety restraints, air bags and other safety systems may be active for up to five minutes after disconnecting the 12-volt battery.

Law Enforcement and Emergency Medical Services

CRASHES DAMAGING THE AREA OF THE HV BATTERY

NOTE: Follow local standard operating procedures (SOPs) for personal protection and safety.

- If you detect leaking fluids, sparks, smoke, flames, increased temperature, gurgling, popping or hissing noises from the HV battery compartment, ventilate passenger area (i.e., roll down windows or open doors) and request fire department response.
- If you detect any unusual odors or experience eye, nose, or throat irritation, move away from the vehicle and evacuate others from the immediate area. Rapid extrication may be needed for injured or trapped occupants.
- Remain a safe distance upwind and uphill from the vehicle and out of the way of oncoming traffic until other appropriately equipped emergency responders arrive.
- Avoid contact with orange high voltage cabling and areas identified as high voltage risk by warning labels
- Be alert. There is a potential for delayed fire with damaged lithium ion batteries.

NOTE: Follow local standard operating procedures (SOPs) for personal protection and safety.

Fire Department

- If you detect leaking fluids, sparks, smoke, flames, increased temperature, gurgling or bubbling sounds from the HV battery compartment, assume there is a battery fire and ventilate the passenger area (i.e., roll down windows or open doors).
- Move away from the vehicle and evacuate others from the immediate area if you
 detect any unusual odors or experience eye, nose, or throat irritation. Wear full
 Personal Protective Equipment (PPE) and Self-Contained Breathing Apparatus (SCBA).
- Be alert. There is a potential for delayed fire with damaged lithium-ion batteries.

FIRES INVOLVING OR EXPOSING THE HV BATTERY

- If you are unable to quickly remove the occupants, use a fire extinguisher to protect them from the flames.
- As with any vehicle fire, the byproducts of combustion can be toxic and all individuals should be directed to move to a safe distance upwind and uphill from the vehicle fire and out of the way of oncoming traffic.

NOTE: If the fire involves a lithium-ion battery, it will require large, sustained volumes of water for extinguishment. Consider defensive tactics and allow fire to burn out.

- If there is active fire, follow local standard operating procedures (SOPs) for vehicle fires. Wear appropriate Personal Protective Equipment (PPE) and Self Contained Breathing Apparatus (SCBA).
- If occupants are still inside the vehicle or trapped, a fire extinguisher may be used to protect the occupants until a hose line is available or the occupants are removed. Consider establishing a water supply to support long-term operation.
- Use a hose line to apply water to extinguish the fire while continuing to cool the HV battery and its casing. Never attempt to penetrate the HV battery or its casing to apply water.
- Avoid contact with orange high voltage cabling and areas identified as high voltage risk by warning labels.
- Be alert. There is a potential for delayed ignition or re-ignition of a lithium-ion battery fire even after it is believed to be extinguished. This may remain an issue until the lithium-ion battery is properly discharged.
- As with any vehicle fire, the byproducts of combustion can be toxic and all individuals should be directed to move to a safe distance upwind and uphill from the vehicle fire and out of the way of oncoming traffic.

Post-Incident

- Always assume the HV battery and associated components are energized and fully charged.
- Ensure that passenger and cargo compartments remain ventilated (i.e., open window, door, or trunk)
- Notify an authorized service center or vehicle manufacturer representative as soon as possible as there may be other steps they can take to secure and discharge the HV battery.
- Do not store a severely damaged vehicle with a lithium-ion battery inside a structure or within 50 feet of any structure or vehicle.
- Request fire department (if appropriate) if you observe leaking fluids, sparks, smoke, flames, or hear gurgling or bubbling from the HV battery.



DOT HS 811 575 January 2012